SCS Global Services *does hereby certify that an independent assessment has been conducted on behalf of:*

Unilin bv, division flooring

Nijverheidslaan 29,, Avelgem, 8580, Belgium

For the following product(s):

See Addendum

The product(s) meet(s) all of the necessary qualifications to be certified for the following claim(s):

FloorScore®

Indoor Air Quality Certified to SCS-105 Version 4.2 – 2023

Conforms to the CDPH/EHLB Standard Method v1.2-2017 (California Section 01350), effective April 1, 2017, for the school classroom and private office parameters when modeled as Flooring.

Measured Concentration of Total Volatile Organic Compounds (TVOC): Between 0.5 – 5.0 mg/m³ (in compliance with CDPH/EHLB Standard Method v1.2-2017)

Registration # SCS-FS-09272

Valid from: September 01, 2026 to August 31, 2027

SCS Global Services is currently the only certification body approved by the Resilient Floor Covering Institute (RFCI) to provide FloorScore® product certification; certified products are only listed on the SCS Green Products Guide, http://www.scsglobalservices.com/certified-green-products-guide.

Diana Kirsanova Phillips, Chief of Staff to the CEO / Chief Assurance Officer
SCS Global Services

Certification Addendum

Unilin bv, division flooring

Certification: Registration # SCS-FS-09272 | Valid from: September 01, 2026 to August 31, 2027

SCS Global Services is currently the only certification body approved by the Resilient Floor Covering Institute (RFCI) to provide FloorScore® product certification; certified products are only listed on the SCS Green Products Guide, http://www.scsglobalservices.com/certified-green-products-guide.

Addendum Conformance: **FloorScore®**

Indoor Air Quality Certified to SCS-105 Version 4.2 – 2023

Conforms to the CDPH/EHLB Standard Method v1.2-2017 (California Section 01350), effective April 1, 2017, for the school classroom and private office parameters when modeled as Flooring.

Measured Concentration of Total Volatile Organic Compounds (TVOC): Between 0.5 – 5.0 mg/m^3 (in compliance with CDPH/EHLB Standard Method v1.2-2017)

Products: **Vinyl Tile:**

Unilin LVT:

Flex Dryback: total thickness between 2 and 2,5 mm with wear layer thickness between 0,3 and 0,55 mm (base, satin, matt)

Flex click: total thickness between 4,2 and 4,5 mm with wear layer thickness between 0,3 and 0,55 mm (base, satin, matt)

Flex Looselay: total thickness between 4 and 4,5 mm with wear layer thickness between 0,2 and 0,7 mm (base, satin, matt)

EVF click: total thickness between 4 and 5 mm class 32 (natural, extra matt)

EVF click: total thickness between 4 and 5 mm class 33 (natural, extra matt)

EVF click with PAD: total thickness between 5 and 6 mm class 32 (natural, extra matt)

EVF click with PAD: total thickness between 5 and 6 mm class 33 (natural, extra matt)